

# DRIP CONTROL ZONE KITS

Kits: **Residential and Light Commercial**  
Flow: **2 to 55 l/min**

## FEATURES

- Convenient kit with all necessary parts
- Highest quality components
- Saves on installation time
- Factory assembled
- Warranty period: 2 years

## FACTORY INSTALLED OPTIONS

- 1.7 or 2.8 bar; 170 or 280 kPa regulator

## USER INSTALLED OPTIONS

- Reclaimed water ID handle for PCZ-101 (P/N 269205)



### PCZ-101

Height: 18 cm  
Width: 7 cm  
Length: 26 cm  
1" BSP (25 mm) inlet x 3/4" outlet

## PCZ-101

- Pressure regulation: 1.7 or 2.8 bar; 170 or 280 kPa
- Flow: 2 to 55 l/min
- Operating pressure: 1.4 to 8.0 bar; 140 to 800 kPa
- Operating temperature: up to 66° C
- 150 mesh; 100 microns stainless steel screen

## SOLENOID OPERATING SPECIFICATIONS

- Heavy-duty solenoid 24 VAC
  - 350 mA inrush current, 190 mA holding current, 60 Hz
  - 370 mA inrush current, 210 mA holding current, 50 Hz

► = *PCZ performance chart on page 220*

MICRO

### DRIP CONTROL ZONE KITS – SPECIFICATION BUILDER: ORDER 1 + 2

1 Model	2 Options
<b>PCZ-101-B</b> = 1" BSP (25mm) PGV globe valve with HFR-100-075 filter and regulator system	<b>25</b> = 1.7 bar; 170 kPa regulator <b>40</b> = 2.8 bar; 280 kPa regulator

#### Examples:

**PCZ-101-B-25** = 1" BSP (25mm) PGV globe valve with HFR-100-075 filter and regulator, 1.7 bar; 170 kPa regulator  
**PCZ-101-B-40** = 1" BSP (25mm) PGV globe valve with HFR-100-075 filter and regulator, 2.8 bar; 280 kPa regulator

PCZ-101 Installed

