

ECO-WRAP®

Subsurface Irrigation: **Under Turf, Gardens, Shrubs, Trees**

FEATURES

- High distribution uniformity surpassed only by the Eco-Mat
- Promotes healthier plant roots
- Eliminates overspray onto sidewalks, buildings, or vehicles
- Ideal for difficult areas between flagstone and pavers
- Use with PLD-Loc or barbed PLD fittings
- Fleece-wrapped professional landscape dripline
- Transports water faster and more uniformly than bare dripline
- Pressure compensating
- Check valves keep the line charged up to 5' and prevent low point drainage
- Fleece fully moistens in less than 3 minutes and conserves water that bare dripline cannot
- Recommended for use with all Hunter Drip Control Zone Kits
- Warranty period: 5 years (plus 2 additional years for environmental stress cracking)



Eco-Wrap

For maximum run length distances for the Eco-Mat® or Eco-Wrap, reference the Maximum Run Length Chart on page 169. Use 0.6 GPH for flow and 12" emitter spacing.

OPERATING SPECIFICATIONS

- Minimum filtration 120 mesh; 125 microns
- Operating pressure range: 15 to 50 PSI
- Compatible with PLD-LOC and 17 mm insert barb fittings

ECO-WRAP TECHNICAL SPECIFICATIONS

ECO-WRAP	17 mm
Flow and Spacing	0.6 GPH and 12"
Roll Length	250'
Operating Pressure	15 to 50 PSI
Minimum Filtration	120 mesh; 125 microns

MICRO