

I-40

Radius: **44' to 76'**
 Flow: **7.6 to 33.7 GPM**
 Inlet: **1"**

FEATURES

- Models stainless riser: 4", 6"
 - Arc setting: 50° to 360°
 - Factory installed rubber cover
 - Nozzle choices: 12
 - Nozzle ranges I-40: #8 to #25
 - Nozzle ranges I-40-ON: #15 to #28
 - Through-the-top arc adjustment
 - QuickCheck™ arc mechanism
 - Water lubricated gear-drive
 - Warranty period: 5 years
- ▶ Opposing nozzle 360 degree model
 - ▶ Automatic arc return
 - ▶ Non-strippable drive
 - ▶ Part- and full-circle in one model
 - ▶ Color-coded nozzles
 - ▶ Reclaimed water ID
 - ▶ Stainless steel riser
 - ▶ Drain check valve (up to 15' of elevation)

OPERATING SPECIFICATIONS

- Radius I-40: 44' to 69'
- Radius I-40-ON: 52' to 76'
- Flow I-40: 7.6 to 29.5 GPM
- Flow I-40-ON: 13.0 to 33.7 GPM
- Recommended pressure range: 40 to 100 PSI
- Operating pressure range: 40 to 100 PSI
- Precipitation rates: 0.4 in/hr approx.
- Nozzle trajectory: 25°

▶ = *Advanced Feature descriptions on page 30*



I-40 Reclaimed

Available as a factory installed option on all models



I-40 High Speed

Available as a factory installed option on all models



I-40-04

Overall height: 7¾"
 Pop-up height: 4"
 Exposed diameter: 2"
 Inlet size: 1"



I-40-06

Overall height: 10¼"
 Pop-up height: 6"
 Exposed diameter: 2"
 Inlet size: 1"

ROTORS

I-40 - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Standard Features	3 Feature Options	4 Nozzle Options
I-40-04-SS = 4" Pop-up I-40-06-SS = 6" Pop-up	Adjustable arc, stainless steel riser, check valve and 6 nozzles	(blank) = No option HS = High speed HS-R = High-speed and reclaimed water ID R = Reclaimed water ID	#8 to #25 = Factory installed nozzle number

I-40-ON - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Opposing Nozzle Model	2 Standard Features	3 Feature Options	4 Nozzle Options
I-40-04-SS-ON = 4" Pop-up I-40-06-SS-ON = 6" Pop-up	Full-circle, opposing nozzle, stainless steel riser, check valve and 6 nozzles	(blank) = No option ON = Full circle opposing nozzles ON-R = Full-circle opposing nozzles and reclaimed water ID HS = High speed HS-R = High speed and reclaimed water ID R = Reclaimed water ID	#15 to #28 = Factory installed nozzle number

Examples:

- I-40-04-SS = 4" Pop-up, adjustable arc, stainless steel riser, with check valve
- I-40-04-SS - **ON-R** - **23** = 4" Pop-up, adjustable arc, stainless steel riser, with check valve, and reclaimed water ID and #23 nozzle
- I-40-06-SS - **15** = 6" Pop-up, adjustable arc, stainless steel riser, with check valve and #15 nozzle

ROTORS

I-40 NOZZLE PERFORMANCE DATA

Nozzle	Pressure PSI	Radius ft	Flow GPM	Precip in/hr	
				■	▲
8 (40) Lt. Brown	40	44	7.6	0.76	0.87
	50	45	8.4	0.80	0.92
	60	46	9.2	0.84	0.97
10 (41) Lt. Green	50	49	10.3	0.83	0.95
	60	50	11.3	0.87	1.00
	70	51	12.2	0.90	1.04
	80	51	13.0	0.96	1.11
13 (42) Lt. Blue	50	50	11.1	0.85	0.99
	60	51	12.3	0.91	1.05
	70	52	13.3	0.95	1.08
	80	53	14.2	0.97	1.12
15 (43) Gray	50	54	13.8	0.91	1.05
	60	55	15.7	1.00	1.15
	70	57	16.6	0.98	1.14
	80	59	18.3	1.01	1.17
23 (44) Dk. Green	60	62	21.3	1.07	1.23
	70	64	23.0	1.08	1.25
	80	65	24.5	1.12	1.29
	90	66	25.9	1.14	1.32
	60	66	23.9	1.06	1.22
25 (45) Dk. Blue	70	67	25.8	1.11	1.28
	80	68	27.7	1.15	1.33
	90	69	29.5	1.19	1.38

I-40 HIGH-SPEED NOZZLE PERFORMANCE DATA

Nozzle	Pressure PSI	Radius ft	Flow GPM	Precip in/hr	
				■	▲
8 (40) Lt. Brown	40	41	7.6	0.87	1.00
	50	41	8.4	0.96	1.11
	60	42	9.2	1.00	1.16
10 (41) Lt. Green	50	45	10.3	0.98	1.13
	60	46	11.3	1.03	1.19
	70	47	12.2	1.06	1.23
	80	47	13.0	1.13	1.31
13 (42) Lt. Blue	50	46	11.1	1.01	1.17
	60	47	12.3	1.07	1.24
	70	48	13.3	1.11	1.28
	80	49	14.2	1.14	1.31
15 (43) Gray	50	51	13.8	1.02	1.18
	60	52	15.7	1.12	1.29
	70	53	16.6	1.14	1.31
	80	54	18.3	1.21	1.40
23 (44) Dk. Green	60	58	21.3	1.22	1.41
	70	59	23.0	1.27	1.47
	80	60	24.5	1.31	1.51
	90	61	25.9	1.34	1.55
	60	59	23.9	1.32	1.53
25 (45) Dk. Blue	70	61	25.8	1.33	1.54
	80	62	27.7	1.39	1.60
	90	63	29.5	1.43	1.65

I-40 NOZZLES



Standard/High-Speed




I-40 Opposing Nozzle 360° Model



I-40 DUAL OPPOSING NOZZLE PERFORMANCE DATA

Nozzle	Pressure PSI	Radius ft	Flow GPM	Precip in/hr	
				■	▲
15 Gray	50	52	13.0	0.46	0.53
	60	54	13.2	0.44	0.50
	70	56	14.4	0.44	0.51
	80	57	15.5	0.46	0.53
18 Red	50	58	13.7	0.39	0.45
	60	59	15.2	0.42	0.49
	70	60	16.6	0.44	0.51
	80	62	17.8	0.45	0.51
20 Dk. Brown	60	63	19.1	0.46	0.53
	70	64	20.9	0.49	0.57
	80	66	22.3	0.49	0.57
	90	66	23.9	0.53	0.61
23 Dk. Green	60	65	20.4	0.46	0.54
	70	66	22.3	0.49	0.57
	80	67	24.0	0.51	0.59
25 Dk. Blue*	90	68	25.6	0.53	0.62
	60	66	22.0	0.49	0.56
	70	68	24.0	0.50	0.58
28 Black	80	69	25.9	0.52	0.60
	90	70	27.2	0.53	0.62
	70	70	28.9	0.57	0.66
	80	72	30.9	0.57	0.66
	90	74	32.9	0.58	0.67
	100	76	33.7	0.56	0.65

I-40 NOZZLES



Opposing

Front



Back



* Factory installed nozzle

Notes:

All precipitation rates calculated for 180° operation. For the precipitation rate for a 360° sprinkler, divide by 2. Precipitation rates for the ON-Opposing Nozzle model are calculated at 360 degrees.