

MLD

MINI LANDSCAPE DRIPLINE

Flow: **0.4-0.85 GPH**
 Surface Irrigation: **Short Runs and Planters**
 Fittings: **All ¼" barb fittings**

FEATURES

- Perfect for short runs and planters
- 100' and 250' rolls
- 6" or 12" emitter spacing
- 250' rolls uncoil from the inside of the roll for easy, no-hassle dispensing
- Offered in both brown or black
- Use with standard ¼" barb fittings
- Warranty period: 2 years

OPERATING SPECIFICATIONS

- 0.250" outside diameter x 0.175" inside diameter
- Operating Pressure: 10-40 PSI
- Materials: LLDPE
- Minimum bending radius: 12"
- Minimum Filtration: 150 mesh; 100 microns

► = Flow chart available on page 155



MLD

MLD Installed



MLD - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1	Model	2	Spacing	3	Length	4	Options
	MLD-05		06 = 6" 12 = 12"		100 = 100' 250 = 250'		BL = Black (blank) = Brown

Example:
 MLD-05 - 12 - 250 = 0.5 GPH mini landscape dripline with 12" spacing in a 250' roll, Brown

MAXIMUM RUN LENGTH

Pressure (PSI)	Emitter Spacing (in.)	
	6	12
25.0	15'	30'
40.0	15'	30'

Notes
 Run lengths based on maintaining consistent flows.

FITTINGS

¼" Barb Fittings:

0.18" barb use with MLD or any vinyl or PE ¼" tubing, UV stabilized materials, and durable single barb connection.



QB-TEE
¼" Barb Tee




QB-ELB
¼" Barb Elbow



QB-CPL
¼" Barb Coupling



QB-CRS
¼" Barb Cross



GP-025
Goof Plug