

# PLD

PROFESSIONAL LANDSCAPE DRIPLINE PLD-CV, PLD-PC, PLD-R

Flow: **0.4, 0.6, 1.0 GPH**  
 Surface Irrigation: **Shrub Rows, Gardens, Tree Rings**

## FEATURES

- Pressure compensating emitters
- Flow rates of 0.4, 0.6, 1.0 GPH
- Emitter spacing at 12", 18", and 24"
- Available without emitters (blank)
- Use with PLD-Loc or barbed PLD fittings
- Strong UV resistance
- Warranty period: 5 years (plus 2 additional years for environmental stress cracking)
- Check valves keep the line charged up to 5' and prevent low-point drainage (PLD-CV only)
- Anti-siphon prevents debris from entering emitters when used subsurface (PLD-CV only)

## OPERATING SPECIFICATIONS

- PLD-CV:
  - Pressure compensating, non-draining emitters
  - Operating pressure range: 15 to 50 PSI
  - Minimum filtration: 120 mesh; 125 microns
- PLD-PC and PLD-R:
  - Pressure compensating
  - Operating pressure range: 10 to 50 PSI
  - Minimum filtration: 120 mesh; 125 microns

► = *Application Rate charts on page 169*



PLD-CV



PLD-PC



PLD-R (Reclaimed)

Optional color for reclaimed water sources

### PLD - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1	Model	2	Spacing	3	Length	4	Options
	PLD-04 = 0.4 GPH Flow	12 = 12"		100 = 100'		CV	
	PLD-06 = 0.6 GPH Flow	18 = 18"		250 = 250'		PC	
	PLD-10 = 1.0 GPH Flow	24 = 24"		500 = 500'		R = Reclaimed *	
	PLD-BLNK = No Emitters			1K = 1,000'			

#### Example:

PLD-04-12-250-CV = 0.4 GPH check valve dripline with 12" spacing in a 250' roll

Notes: \* 100' rolls available only in models PLD-CV-100, PLD-06-12-100, PLD-10-12-100, and PLD-10-18-100. Reclaimed models available in 0.6 and 1.0 GPH only and do not contain check valves.

### PLD Installed



MICRO