

PRS40

PRESSURE REGULATED

Models: **Shrub, 10 cm, 15 cm, 30 cm**
 Pressure Regulation: **2.8 bar; 280 kPa**

FEATURES

- Models: Shrub, 10 cm, 15 cm, 30 cm
- Grey identification cap for easy field ID
- Innovative directional flush plug design
- Drain check valve installed with up to 4.3 m of elevation comes standard
- 15 cm and 30 cm models come standard as no side inlet, ensuring proper installation with check valve
- Warranty period: 5 years
- ▶ Co-molded wiper seal
- ▶ Heavy-duty spring
- ▶ Industry's strongest spray body
- ▶ Innovative seal design
- ▶ Pro-Spray® check valve
- ▶ Pressure regulated to 2.8 bar
- ▶ FloGuard™ technology

OPERATING SPECIFICATIONS

- Operational pressure range: 1.0 to 7.0 bar; 100 to 700 kPa

FACTORY INSTALLED OPTIONS

- Reclaimed water ID cap
- FloGuard technology available for check valve models

USER INSTALLED OPTIONS

- Reclaimed water ID cap (P/N 458562)
- Snap-on reclaimed cover (P/N PROS-RC-CAP)
- ▶ = *Advanced Feature descriptions on page 64*



PRS40 Reclaimed

PRS40 models include optional factory-installed purple reclaimed caps.



Related Solutions: MP Rotator

PRS40 is designed specifically for the MP Rotator.



PROS-00-PRS40
 Retracted height: 11 cm
 Inlet size: ½"



PROS-04-PRS40-CV
 Retracted height: 15.5 cm
 Pop-up height: 10 cm
 Exposed diameter: 5.7 cm
 Inlet size: ½"



PROS-06-PRS40-CV
 Retracted height: 22.5 cm
 Pop-up height: 15 cm
 Exposed diameter: 5.7 cm
 Inlet size: ½"



PROS-12-PRS40-CV
 Retracted height: 41 cm
 Pop-up height: 30 cm
 Exposed diameter: 5.7 cm
 Inlet size: ½"

SPRAYS

PRS40 – SPECIFICATION BUILDER: ORDER 1 + 2

1 Model	2 Specialty Options
<p>PROS-00-PRS40 = 2.8 bar regulated shrub adapter</p> <p>PROS-04-PRS40-CV = 2.8 bar regulated 10 cm Pop-up with drain check valve</p> <p>PROS-06-PRS40-CV = 2.8 bar regulated 15 cm Pop-up with drain check valve</p> <p>PROS-12-PRS40-CV = 2.8 bar regulated 30 cm Pop-up with drain check valve</p>	<p>(blank) = No option</p> <p>R = Factory-installed reclaimed body cap</p> <p>F = FloGuard technology</p> <p>F-R = FloGuard technology with reclaimed body cap</p>

Examples:

- PROS-04-PRS40-CV = 10 cm Pop-up regulated at 2.8 bar, drain check valve
- PROS-06-PRS40-CV-F = 15 cm Pop-up regulated at 2.8 bar, drain check valve, with FloGuard technology
- PROS-12-PRS40-CV-R = 30 cm Pop-up regulated at 2.8 bar, drain check valve, reclaimed body cap