

PRS40

PRESSURE REGULATED

Models: **Shrub, 4", 6", 12"**
Pressure Regulation: **40 PSI**

FEATURES

- Models: Shrub, 4", 6", 12"
- Gray identification cap for easy field ID
- Innovative directional flush plug design
- 6" and 12" models come standard as no side inlet, ensuring proper installation with check valve
- Drain check valve installed (14' of elevation) comes standard
- Warranty period: 5 years
- ▶ Co-molded wiper seal
- ▶ Heavy-duty spring
- ▶ Industry's strongest spray body
- ▶ Innovative seal design
- ▶ Pro-Spray check valve
- ▶ Pressure regulated to 40 PSI
- ▶ FloGuard™ technology

OPERATING SPECIFICATIONS

- Operational pressure range: 15 to 100 PSI

FACTORY INSTALLED OPTIONS

- Reclaimed water ID cap
- FloGuard technology available for check valve models

USER INSTALLED OPTIONS

- Reclaimed water ID cap (P/N 458562)
- Snap-on reclaimed cover (P/N PROS-RC-CAP)
- ▶ = *Advanced Feature descriptions on page 52*



PRS40 Reclaimed

PRS40 models include optional factory-installed purple reclaimed caps



Related Solutions: MP Rotator

PRS40 is designed specifically for the MP Rotator®



PROS-00-PRS40

Retracted height: 4½"
Inlet size: ½"



PROS-04-PRS40-CV

Retracted height: 5⅞"
Pop-up height: 4"
Exposed diameter: 2¼"
Inlet size: ½"



PROS-06-PRS40-CV

Retracted height: 8¾"
Pop-up height: 6"
Exposed diameter: 2¼"
Inlet size: ½"



PROS-12-PRS40-CV

Retracted height: 16⅞"
Pop-up height: 12"
Exposed diameter: 2¼"
Inlet size: ½"

PRS40 – SPECIFICATION BUILDER: ORDER 1 + 2

1 Model	2 Specialty Options
<p>PROS-00-PRS40 = 40 PSI regulated shrub adapter</p> <p>PROS-04-PRS40-CV = 40 PSI regulated 4" pop-up with drain check valve</p> <p>PROS-06-PRS40-CV = 40 PSI regulated 6" pop-up with drain check valve</p> <p>PROS-12-PRS40-CV = 40 PSI regulated 12" pop-up with drain check valve</p>	<p>(blank) = No option</p> <p>R = Factory-installed reclaimed body cap</p> <p>F = FloGuard technology</p> <p>F-R = FloGuard technology with reclaimed body cap</p>

Examples:

- PROS-04-PRS40-CV = 4" Pop-up regulated at 40 PSI, drain check valve
- PROS-06-PRS40-CV-F = 6" Pop-up regulated at 40 PSI, drain check valve, with FloGuard technology
- PROS-12-PRS40-CV-R = 12" Pop-up regulated at 40 PSI, drain check valve, reclaimed body cap

SPRAYS