

SUPPLY TUBING

½" POLYETHYLENE PROFESSIONAL TUBING

Uses: **Water transportation**
Size: **OD 0.700" x ID 0.600"**

FEATURES

- 0.700" outside diameter x 0.600" inside diameter
- Connect using PLD-Loc fittings or standard 700 series compression fittings
- Made with linear low density UV-resistant polyethylene
- Thicker wall, commercial grade
- Warranty period: 2 years

OPERATING PRESSURE

- 0 to 60 PSI



½" PE Tubing

½" PE TUBING - SPECIFICATION BUILDER: ORDER 1 + 2 + 3

1 Model	2 Tubing Diameter	3 Length
TWPE = Thick-Walled Polyethylene Tubing	700 = 0.700" outside diameter	100 = 100' 250 = 250' 500 = 500' 1K = 1,000'

Example:

TWPE-700 - 250 = ½" polyethylene tubing in a 250' roll

DISTRIBUTION TUBING

¼" POLYETHYLENE AND VINYL TUBING

Uses: **Water transportation**
Size: **OD 0.250" x ID 0.170"**

FEATURES

- 0.250" outside diameter x 0.170" inside diameter
- Connect using standard ¼" fittings (0.18" barbs)
- Offered in vinyl or polyethylene
- UV Resistant materials
- Polyethylene is better choice in warm climates
- Vinyl is more flexible and useful in cold climates
- Warranty: 2 years

OPERATING PRESSURE

- 0 to 60 PSI



¼" Tubing

¼" TUBING - SPECIFICATION BUILDER: ORDER 1 + 2 + 3

1 Model	2 Tubing Diameter	3 Length
HQPE = Polyethylene Tubing	250 = 0.250" outside diameter	100 = 100'
HQV = Vinyl Tubing		250 = 250'
		1K = 1,000'

Example:

HQPE-250 - 1K = ¼" polyethylene tubing in a 1,000' roll

MICRO