

# RZWS

Size: **25, 45, 90 cm**  
Flow: **0.9 l/min or 1.9 l/min**

## FEATURES

- Built-in Hunter Swing Joint for direct installation to ½" PVC fitting
- Hunter pressure-compensating bubbler for precise watering
- Pre-assembled watering system for fast installation
- Patented StrataRoot™ baffles divert water to root zone while adding strength to the unit
- Vandal-proof locking cap

## FACTORY INSTALLED OPTIONS

- Check valve
- Locking reclaimed purple cap

## USER INSTALLED OPTIONS

- Fabric sleeve that helps prevent soil intrusion in sandy areas for 45 cm and 90 cm models (P/N RZWS-SLEEVE)
- Replacement cap for 45 and 90 cm models (P/N 913300SP)
- Locking reclaimed purple cap for 45 and 90 cm models (P/N 913301SP)
- Reclaimed water purple cap for 25 cm (P/N RZWS10-RCC)

## OPERATING SPECIFICATIONS

- Bubbler flow rates: 0.9 l/min or 1.9 l/min
- Recommended pressure range: 1.0 to 4.8 bar; 100 to 480 kPa



**RZWS-10**  
Diameter: 5.1 cm  
Length: 25 cm

**RZWS-18**  
Tube Diameter: 7.6 cm  
Cap Diameter: 12 cm  
Length: 45 cm

**RZWS-36**  
Tube Diameter: 7.6 cm  
Cap Diameter: 12 cm  
Length: 90 cm

**Reclaimed models available**  
Add **-R** to model number



RZWS patented StrataRoot™ baffles



### RZWS - SPECIFICATION BUILDER: Order 1 + 2 + 3

1 Model	2 Bubbler Flow Rate	3 Options
RZWS-10 = 25 cm Root Zone Watering System	25 = 0.9 l/min	(blank) = No option
RZWS-18 = 45 cm Root Zone Watering System	50 = 1.9 l/min	CV = Check valve
RZWS-36 = 90 cm Root Zone Watering System	(blank) = no bubbler or swing joint	R = Reclaimed cap
		CV-R = Check valve with reclaimed cap

#### Examples:

- RZWS-18 - 25 - CV = 45 cm Root Zone Watering System at 0.9 l/min, with check valve
- RZWS-10 - 50 - R = 25 cm Root Zone Watering System at 1.9 l/min, with reclaimed cap
- RZWS-36 - 25 - CV-R = 90 cm Root Zone Watering System at 0.9 l/min, with check valve and reclaimed cap

### ADDITIONAL OPTIONS (SPECIFY SEPARATELY)

RZWS-SLEEVE = Field-installed sleeve made from filter fabric

MICRO

# RZWS-E

Size: **25, 45, 90 cm**  
Flow: **0.9 l/min or 1.9 l/min**

## FEATURES

- Built-in Hunter Swing Joint for direct installation to ½" PVC fitting
- Hunter pressure-compensating bubbler for precise watering
- Pre-assembled watering system for fast installation
- Top serviceable cap design

## OPERATING SPECIFICATIONS

- Bubbler flow rates: 0.9 l/min or 1.9 l/min
- Recommended pressure range: 1.0 to 4.8 bar; 100 to 480 kPa



**RZSW-E-18**  
Diameter: 7.6 cm  
Length: 45 cm

**RZWS-E-36**  
Diameter: 7.6 cm  
Length: 90 cm

### RZWS-E - SPECIFICATION BUILDER: Order 1 + 2

1 Model	2 Bubbler Flow Rate
<b>RZWS-E-18</b> = 45 cm Root Zone Watering System	<b>25</b> = 0.9 l/min
<b>RZWS-E-36</b> = 90 cm Root Zone Watering System	<b>50</b> = 1.9 l/min

#### Examples:

**RZWS-E-18 - 50** = 45 cm Root Zone Watering System, 1.9 l/min bubbler  
**RZWS-E-36 - 25** = 90 cm Root Zone Watering System, 0.9 l/min bubbler



#### RZB

The RZB is an accessory for small trees and shrubs that assists irrigation systems in delivering water to the roots.

- Solid mesh tube with perforated top to complement overhead or drip irrigation systems
- Allows oxygen and natural precipitation to reach the root zone
- Easy installation that directs overhead and drip irrigation to the root zone



Diameter: 5 cm  
Length: 23 cm