

THIS RUGGED ROTOR CAN STAND UP TO ANY COMMERCIAL JOB.

FEATURES

- Models: 4", 6"
- Arc setting: 50 to 360 degrees
- Nozzle choices: 12
- Nozzle range: #4 to #28
- Factory installed rubber cover
- Through-the-top arc adjustment
- Quick check arc mechanism
- Water lubricated gear-drive
- Warranty period: 5 years

ADVANCED FEATURES

- Automatic arc return
- Non-strippable drive
- Part- and full-circle in one model
- Color coded nozzles
- Reclaimed water ID (optional)
- Stainless steel riser (optional)
- Drain check valve (up to 10' of elevation)

OPERATING SPECIFICATIONS

Radius: 37' to 71'
 Flow rate: 3.8 to 31.5 GPM
 Recommended pressure range: 40 to 100 PSI
 Operating pressure range: 40 to 100 PSI
 Precipitation rates: 0.4 in/hr approx.
 Nozzle trajectory: 25 degrees

FACTORY INSTALLED OPTIONS

Nozzles: #4 to #28
 Reclaimed water ID cover
 High speed rotation model (stainless steel only)



I-25-04: Overall height: 7 7/8"
 Pop-up height: 4"
 Exposed diameter: 1 1/4"
 Inlet size: 1" female NPT

I-25-06: Overall height: 10 1/4"
 Pop-up height: 6"
 Exposed diameter: 1 1/4"
 Inlet size: 1" female NPT

SPECIFICATIONBUILDER

www.hunterindustries.com/I25

MODELS	STANDARD FEATURES	FEATURE OPTIONS	NOZZLE OPTIONS
I-25-04 = 4" pop-up I-25-06 = 6" pop-up	Adjustable arc, plastic riser, check valve, and 5 nozzles	R, B	#4 to #28 = Factory installed nozzle number
I-25-04-SS = 4" pop-up I-25-06-SS = 6" pop-up	Adjustable arc, stainless steel riser, check valve, and 5 nozzles	R, HS, HS-R, B	#4 to #28 = Factory installed nozzle number

EXAMPLES

I-25-04	4" pop-up, adjustable arc
I-25-04-SS - R - 18	4" pop-up, adjustable arc, stainless steel riser, reclaimed water ID, and #18 nozzle
I-25-06-SS	6" pop-up, adjustable arc, stainless steel riser