

IRRIGATION LEGEND

PRODUCT DESCRIPTION

HUNTER I-35-06-SS-XX NOZZLE AS SHOWN HUNTER I-35-06-SS-XX NOZZLE AS SHOWN

NOZZLE PERFORMANCE: #13 @ 40 PSI - 12.4 GPM 53' RADIUS #15 @ 40 PSI - 14.7 GPM 55' RADIUS

HFS HUNTER FLOW SENSOR IN LINE SIZED FLOW CLIK TEE "FCT"

IRRIGATION NOTES

- SPRINKLER LOCATIONS ARE TO SCALE
 PIPE LOCATIONS ARE DIAGRAMMATIC
 ALL SPRINKLERS TO BE INSTALLED ON 1" SCH 80 SWING JOINTS 4. ALL COMPONENTS TO BE INSTALLED AS PER MANUFACTURERS
- RECOMMENDATIONS
- 5. MAINLINE DEPTH TO BE NO LESS THAN 18"
 6. LATERAL DEPTH TO BE NO LESS THAN 16"
 7. ELECTRIC CONTROL VALVES TO BE COVERED WITH 12" VALVE BOX B. LOCATE VALVES/QCV'S OUT OF HIGH TRAFFIC AREAS 9. WIRE SPLICE CONNECTIONS TO BE WATERPROOF
- 10. QCV TO BE LOCATED IN 10" VALVE BOX
 11. ALL SLEEVES TO BE 2X PIPE RUN THROUGH THEM
- INSTALL ALL COMPONENTS AS PER LOCAL, STATE,
- 13. REFER TO HUNTER INSTALLATION DETAILS
 14. REFER TO HUNTER CATALOG FOR PERSMANCE SPECIFICATIONS
 15. ADD HUNTER "FS" FOR DIRTY WATER VALVE
 16. ADD HUNTER "AS" FOR PRESSURE REGULATED VALVE

VALVE ID GUIDE

ZONE A1 A2 A3 A4 A5 A6 A6 A7 A10 A11 A11 A12 A13

TEM PERFORMANCE DATA

Hunder Industries offers this plan as a general guide for estimating purposes and offers no indemnity, expressed or impilled, for projects Installed from this plan. Because of the many variables of every system and of every site we recommend that a qualified irrigation designer be consulted. PR 98 98 98 98 98 11.07 11.07 11.07 11.07 15.44 79 79 77 77 77 77 77

OFFICIAL BASEBALL FIELD

I-35LP FIVE ROW DESIGN LOOPED MAINLINE



Hunter Industries 1940 Diamond Street San Marcos, California 92078 SpecPro Technical Assistance 1-800-319-4796 www.HunterIndustries.com SHEET

유