

## IRRIGATION LEGEND

WATER REQUIREMENT

PRODUCT DESCRIPTION

14.7 A7

25

● HUNTER I-35-06-SS-XX NOZZLE AS SHOWN
● HUNTER I-35-06-SS-XX NOZZLE AS SHOWN
NOZZLE PERFORMANCE:
#13 @ 40 PSI - 12.4 GPM 53' RADIUS
#15 @ 40 PSI - 14.7 GPM 55' RADIUS

HFS HUNTER FLOW SENSOR IN LINE SIZED FLOW CLIK TEE "FCT"

## IRRIGATION NOTES

- 1. SPRINKLER LOCATIONS ARE TO SCALE

- 4. ALL COMPONENTS TO BE INSTALLED AS PER MANUFACTURERS PIPE LOCATIONS ARE DIAGRAMMATIC
  ALL SPRINKLERS TO BE INSTALLED ON 1" SCH 80 SWING JOINTS
- 9. WIRE SPLICE CONNECTIONS TO BE WATERPROOF ELECTRIC CONTROL VALVES TO BE COVERED WITH 12" VALVE BOX LOCATE VALVES/QCV'S OUT OF HIGH TRAFFIC AREAS
- 10. QCV TO BE LOCATED IN 10" VALVE BOX
  11. ALL SLEEVES TO BE 2X PIPE RUN THROUGH THEM
  12. INSTALL ALL COMPONENTS AS PER LOCAL, STATE,

- 13. REFER TO HUNTER INSTALLATION DETAILS
  14. REFER TO HUNTER CATALOG FOR PERFORMANCE SPECIFICATIONS
  15. ADD HUNTER "FS" FOR DIRTY WATER VALVE
  16. ADD HUNTER "AS" FOR PRESSURE REGULATED VALVE

## FLOW PR Б

## SYSTEM PERFORMANCE DATA SIZE

thunder industries offers this plan as a general guide for estimating purposes and offers no indemnity expressed or implied, for projects installed from this plan. Because of the many variables of every system and of every site we recommend that a qualified irrigation designer be consulted.

OF 1

SHEET

Hunter Industries 1940 Dlamond Street San Marcos, Callfornia 92078 SpecPro Technical Assistance 1-800-319-4796 www.HunterIndustries.com

OFFICIAL BASEBALL FIELD

I-35LP FIVE ROW DESIGN

