

IRRIGATION LEGEND PRODUCT DESCRIPTION

HUNTER I-35-06-SS-XX, NOZZLE AS SHOWN HUNTER I-35-06-SS-XX, NOZZLE AS SHOWN NOZZLE PERFORMANCE: HUNTER ICV/IBV ELECTRIC CONTROL VALVE SIZE AS SHOWN #30 @ 80 PSI - 28.7 GPM 70' RADIUS

HUNTER HQ-44-XX-AW QUICK COUPLER VALVE (OPTIONAL)
HUNTER IC-1200 SOLID STATE METAL CABINET CONTROLLER
HUNTER SOLAR-SYNG-SEN ON SITE WEATHER SENSOR

BACKFLOW PREVENTER SIZED TO SYSTEM GPM WATER METER MINIMUM SIZE @ 115 GPM IS 2.0"

MAINLINE PIPE LATERAL PIPE

ISOLATION VALVE LINE SIZED SLEEVING

|| ||⊗


IRRIGATION NOTES

- SPRINKLER LOCATIONS ARE TO SCALE
 PIPE LOCATIONS ARE DIAGRAMMATIC
 ALL SPRINKLERS TO BE INSTALLED ON 1" SCH 80 SWING JOINTS
 ALL COMPONENTS TO BE INSTALLED AS PER MANUFACTURERS
 RECOMMENDATIONS
- 5. MAINLINE DEPTH TO BE NO LESS THAN 18"
 6. LATERAL DEPTH TO BE NO LESS THAN 16"
 7. ELECTRIC CONTROL VALVES TO BE COVERED WITH 12" VALVE BOX
 8. LOCATE VALVES/QCV'S OUT OF HIGH TRAFFIC AREAS
 9. WIRE SPLICE CONNECTIONS TO BE WATERPROOF
 10. QCV TO BE LOCATED IN 10" VALVE BOX
 11. ALL SLEEVES TO BE 2X PIPE RUN THROUGH THEM
- 12. INSTALL ALL COMPONENTS AS PER LOCAL, STATE
- FEDERAL CODES

13. REFER TO HUNTER INSTALLATION DETAILS
14. REFER TO HUNTER CATALOG FOR PERFORMANCE SPECIFICATIONS

15. ADD HUNTER "FS" FOR DIRTY WATER VALVE
16. ADD HUNTER "AS" FOR PRESSURE REGULATED VALVE

SYSTEM PERFORMANCE DATA



thurier industries offers this plan as a general guide for estimating purposes and offers to indemnity, expressed or implied, for projects itselfs off com this plan. Because of the many variables of every system and of every site we recommend that a qualified infigation designer be consulted.

1 OF 1 SHEET Hunter Industries 1940 Diamond Street San Marcos, California 92078 SpecPro Technical Assistance 1-800-319-4796 www.HunterIndustries.com

LACROSSE FIELD

I-25 FOUR ROW DESIGN

