

IRRIGATION LEGEND

 $\mathbf{\Phi}\mathbf{\Phi}$ PRODUCT DESCRIPTION

HUNTER 140-04-SS-B-XXI-140-06-SS-B-XX, NOZZLE AS SHOWN
HUNTER 140-04-SS-B-XXI-140-06-SS-B-XX, NOZZLE AS SHOWN
NOZZLE PERFORMANCE:
#33 @ 5.5 Bars - 92.7 l/min 19.8m Radius
HUNTER IC/JIBV ELECTRIC CONITROL VALVE SIZE AS SHOWN
HUNTER IC/JIBV ELECTRIC CONITROL VALVE SIZE AS SHOWN
HUNTER HC/23-XX-AW QUICK COUPLER VALVE (OPTIONAL)

HUNTER CJ-300-M SOLID STATE METAL CABINET CONTROLLER
HUNTER SOLAR-SYNC-SEN ON SITE WEATHER SENSOR
M WATER METER MINIMUM SIZE @ 185 l/min is 50mm

M WATER METER MINIMUM SIZE @ 175 SYSTEM l/min

M MATER METER MINIMUM SIZE @ 175 SYSTEM l/min

M MATER METER MINIMUM SIZE @ 175 SYSTEM l/min

M MATER METER MINIMUM SIZE @ 175 SYSTEM l/min

M MATER METER MINIMUM SIZE @ 175 SYSTEM l/min

HUNTER ICV/IBV ELECTRIC CONT HUNTER PO-23-XX-AW QUICK CO WHUNTER C-600-M SOLID STATE N HUNTER C-500-M SOLID STATE N HUNTER SOLAR-SYNC-SEN ON SI MAYER METER MINIMUM SIZE QUE BACKELOW PREVENTER SIZED TO MAINLINE PIPE LATERAL PIPE SLEEVING SIZED SOLATION VALVE LINE SIZED HIST HUNTER FLOW SENSOR IN LINE S

HUNTER FLOW SENSOR IN LINE SIZED FLOW CLIK TEE "FCT"

IRRIGATION NOTES

- SPRINKLER LOCATIONS ARE TO SCALE
 PIPE LOCATIONS ARE DIAGRAMMATIC
 ALL SPRINKLERS TO BE INSTALLED ON 32mm SCH 80 SWING
 JOINTS
- 4. ALL COMPONENTS TO BE INSTALLED AS PER MANUFACTURERS RECOMMENDATIONS
- 5. MAINLINE DEPTH TO BE NO LESS THAN 460mm
 6. LATERAL DEPTH TO BE NO LESS THAN 410mm
 7. ELECTRIC CONTROL VALVES TO BE COVERED WITH 12" VALVE
- BOX

 8. LOCATE VALVES/QCV'S OUT OF HIGH TRAFFIC AREAS

 9. WIRE SPLICE CONNECTIONS TO BE WATERPROOF

 10. QCV TO BE LOCATED IN 10" VALVE BOX

 11. ALL SLEEVES TO BE 2X PIPE RUN THROUGH THEM

 12. INSTALL ALL COMPONIENTS AS PER LOCAL, STATE,
- FEDERAL CODES
- 13. REFER TO HUNTER INSTALLATION DETAILS
 14. REFER TO HUNTER CATALOG FOR PERFORMANCE SPECIFICATIONS

15. ADD HUNTER "FS" FOR DIRTY WATER VALVE
16. ADD HUNTER "AS" FOR PRESSURE REGULATED VALVE

SYSTEM PERFORMANCE DATA SIZE FLOW m^o/hr Umin 11.1 185 11.1 185 11.1 185 11.1 186 5.5 92.7 PR 27.8 57.3 57.3 13.8 80 80 D 111111 SC

ZONE A1 A2 A3 A3 A5

WATER REQUIREMENT

WATER REQUIREMENT AT
-FIELD ELEVATION
-WITHIN 30m OF FIELD
-DOWNSTREAM OF
BACKFLOW
IS 185 l/min @ 6.22 Bars

STATION NUMBER PRECIPITATION RATE mm/h VALVE SIZE

VALVE ID GUIDE

Hunter Industries 1940 Diamond Street San Marcos, California 92078 SpecPro Technical Assistance 1-800-319-4796 www.HunterIndustries.com

LAWN BOWLING

I-40 DESIGN

SHEET 유 1