

IRRIGATION LEGEND

PRODUCT DESCRIPTION

HUNTER 140-04-SS-ON-B-XXII-40-06-SS-ON-B-XX
HUNTER 140-04-SS-B-XXII-40-06-SS-B-XX
NOZZIE PERFORMANCE:
NOZZIE PERFORMANCE:
#15 @ 5.5 Bars - 88.9 I/min 120.1m RADIUS
#20 @ 5.5 Bars - 84.7 I/min 20.1m RADIUS
#20 @ 5.5 Bars - 84.7 I/min 20.1m RADIUS
#20 @ 5.5 Bars - 84.7 I/min 20.1m RADIUS

HUNTER HQ-44-XX-AW QUICK COUPLER VALVE

炒 • **⊕**

HUNTER SOLAR SYNC-SEN ON SITE WEATHER SENSOR WATER METER MINIMUM SIZE @ 344 I/min IS 63mm HUNTER ACC-1200-M SOLID STATE METAL CABINET CONTROLLER

BACKFLOW PREVENTER SIZED TO SYSTEM Imin MAINLINE PIPE LATERAL PIPE

SLEEVING

∄⊗

ISOLATION VALVE LINE SIZED

HUNTER FLOW SENSOR IN LINE SIZED FLOW CLIK TEE "FCT"

IRRIGATION NOTES

- SPRINKLER LOCATIONS ARE TO SCALE

 PIPE LOCATIONS ARE DIAGRAMMATIC

 ALL SPRINKLERS TO BE INSTALLED ON 32mm SCH 80

 SWING JOINTS

 ALL COMPONENTS TO BE INSTALLED AS PER
- MANUFACTURER RECOMMENDATIONS
- MAINLINE DEPTH TO BE NO LESS THAN 460mm
 LATERAL DEPTH TO BE NO LESS THAN 410mm
 ELECTRIC CONTROL VALVES TO BE COVERED WITH 12"

VALVE BOX

- 8. LOCATE VALVES/OCV'S OUT OF HIGH TRAFFIC AREAS 9. WIRE SPLICE CONNECTIONS TO BE WATERPROOF 10. QCV TO BE LOCATED IN 10" VALVE BOX
 11. ALL SLEEVES TO BE 2X PIPE RUN THROUGH THEM
- 13. REFER TO HUNTER INSTALLATION DETAILS
 14. REFER TO HUNTER CATALOG FOR PERFORMANCE SPECIFICATIONS FEDERAL CODES

12. INSTALL ALL COMPONENTS AS PER LOCAL, STATE,

15. ADD HUNTER "FS" FOR DIRTY WATER VALVE
16. ADD HUNTER "AS" FOR PRESSURE REGULATED VALVE

SYSTEM PERFORMANCE DATA

ZONE

Z _I	2	2	Ŋ	Ŋ	2	٠ - ۲	Ŋ	٠ - ١	Ŋ	2	SIZE
20.3	20.3	20.3	20.3	20.3	16.5	8 3	20.6	8 3	16.5	20.6 J/min 20.6 344	7
339	339	339	339	339	275	138	344	138	275	344	Q.
14.5	14.5	14.5	14.5	14.5	23.1	50.7	23.1	50.7	23.1	23.1	굿
.86	86	86	86	86	84	84	84	84	84	84	5
1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	SC (10% WINDOW)

VALVE ID GUIDE STATION NUMBER

19.0 PRECIPITATION RATE mm/h VALVE SIZE

Hunter Industries offers this plan as a general guide for estimating purposes and offers no indemnity, expressed or implied, for projects installed from this plan. Because of the many variables of every system and of every site we recommend that a qualified imgation designer be consulted.

WATER REQUIREMENT

WATER REQUIREMENT AT:
-FIELD ELEVATION
-WITHIN 30M OF FIELD
-DOWNSTREAM OF
BACKFLOW
IS 344 I/min @ 6.01 Bars

MULTI-PURPOSE FIELD

I-40 SIX ROW DESIGN LOOPED MAINLINE



SHEET 유

Hunter Industries 1940 Dlamond Street
San Marcos, California 92078
SpecPro Technical Assistance
1-800-319-4796
www.HunterIndustries.com