

12. INSTALL ALL COMPONENTS AS PER LOCAL, STATE, FEDERAL CODES
13. REFER TO HUNTER INSTALLATION DETAILS
14. REFER TO HUNTER CATALOG FOR PERFORMANCE SPECIFICATIONS
15. ADD HUNTER "FS" FOR DIRTY WATER VALVE
16. ADD HUNTER "AS" FOR PRESSURE TO THE PRESSURE T

|| ||

SLEEVING

ISOLATION VALVE LINE SIZED

HUNTER ICV/IBV ELECTRIC CONTROL VALVE SIZE AS SHOWN HUNTER HQ-44-XX-AW QUICK COUPLER VALVE (OPTIONAL) HUNTER IC-1200-M SOLID STATE METAL CABINET CONTROLLER HUNTER SOLAR-SYNC-SEN ON SITE WEATHER SENSOR WATER METER MINIMUM SIZE @ 246 I/min IS 50mm BACKFLOW PREVENTER SIZED TO SYSTEM I/min MAINLINE PIPE

5. MAINLINE DEPTH TO BE NO LESS THAN 460mm
6. LATERAL DEPTH TO BE NO LESS THAN 410mm
7. ELECTRIC CONTROL VALVES TO BE COVERED WITH 12" VALVE BOX
8. LOCATE VALVES/QCV'S OUT OF HIGH TRAFFIC AREAS
9. WIRE SPLICE CONNECTIONS TO BE WATERPROOF

10. QCV TO BE LOCATED IN 10" VALVE BOX
11. ALL SLEEVES TO BE 2X PIPE RUN THROUGH THEM
12. INSTALL ALL COMPONENTS AS PER LOCAL, STATE,

SPRINKLER LOCATIONS ARE TO SCALE
 PIPE LOCATIONS ARE DIAGRAMMATIC
 ALL SPRINKLERS TO BE INSTALLED ON 32mm SCH 80 SWING JOINTS
 ALL COMPONENTS TO BE INSTALLED AS PER MANUFACTURERS

RECOMMENDATIONS

HUNTER I-35-06-SS-B-XX, NOZZLE AS SHOWN HUNTER I-35-06-SS-B-XX, NOZZLE AS SHOWN NOZZLE PERFORMANCE: #15 @ 5.5 Bars - 61.5 I/min 17.7m RADIUS

PRODUCT DESCRIPTION

SHE 유 Ш

Hunter Industries 1940 Diamond Street San Marcos, California 92078 SpecPro Technical Assistance 1-800-319-4796 www.HunterIndustries.com

SOCCER FIELD 60x90M

Hunder

I-35 FOUR ROW DESIGN

5m

Hunter Industries offers this plan as a general guide for from this plan. Because of the many variables of every