

# WATERPROOF WIRE CONNECTOR

Use this approved waterproof connector for EZ Decoder and all above-grade solenoid and sensor wiring connections.

## KEY BENEFITS

- 100% silicone-based sealant protects against moisture and corrosion
- Designed as a single-use only connection
- UL Listed for 600 V and 486G for use in damp/wet locations or above-grade applications
- Easy to apply, pre-filled twist-on wire connectors
- Eliminates the need for heat-shrink or excessive taping
- Not for use in continual submersion applications, use DBRY-6
- Approvals: UL, cUL, FCC, CE, RCM, RoHS, ISED



### Waterproof Wire Connector

Height: 3.5 cm  
 Minimum wire: 3 #0.8 mm<sup>2</sup>  
 Maximum wire: 2 #6 mm<sup>2</sup> with 1 #3 mm<sup>2</sup>

WIRE CONNECTOR	
Model	Description
WC100	Bulk 100 connectors in canister

### WC100 WIRE CONNECTOR



# WATERPROOF SPLICE KIT

Use this approved splice kit for all direct-burial two-wire ICD and legacy DUAL™ Decoder wiring connections, as well as Pilot™ Two-Way Modules.

## KEY BENEFITS

- UL Listed for 600 V and 486D for use in damp/wet location or direct-burial applications
- Waterproof, corrosion-proof, UV-rated, and impact resistant
- Snap-fit lid provides strain relief and three-wire exits
- Pre-filled with silicone that never hardens
- Two part system includes red/yellow winged wire connector and silicone-filled tube
- Compatible with EZ Decoder connections, but not a requirement
- Approvals: UL, cUL, FCC, CE, RCM, RoHS, ISED



### Waterproof Splice Kit

Height: 9.5 cm  
 Minimum wire: 2-7 #0.8 mm<sup>2</sup>  
 Maximum wire: 2-3 #6 mm<sup>2</sup>

DBRY-6 SPLICE KIT	
Model	Description
DBRY100	Bulk 100 connectors (100 tubes loose in box, plus inner box with 100 Wire Nuts)
DBRY2X25	25 x 2-packs (2 tubes and 2 Wire Nuts in a plastic bag, x 25 units)

### DBRY-6 WATERPROOF SPLICE KIT

