

SPRAY ACCESSORIES

Spray accessories provide additional flexibility for installation and maintenance of spray systems.

SJ SWING JOINTS

Features

- Unique swivel ells on both ends for easy installation in any configuration
- Airtight connection points for long-term reliability

Models

- SJ-506: ½" threaded x 6" length standard
- SJ-7506: ½" x ¾" threaded x 6" length
- SJ-706: ¾" threaded x 6" length
- SJ-512: ½" threaded x 12" length
- SJ-7512: ½" x ¾" threaded x 12" length
- SJ-712: ¾" threaded x 12" length

Operating Specifications

- Pressure-rated to 150 PSI
- Warranty period: 2 years

HUNTER SPIRAL BARB ELBOWS

Features

- Improved bigger, stronger design
- Compatible with Flex^{SG} and other brands for a customized swing joint
- Spiral to barb design for easier installation
- Acetal material for sharp barbs

Models

- HSBE-050: ½" male thread x spiral barb elbow
- HSBE-075: ¾" male thread x spiral barb elbow

Operating Specifications

- Operating pressure: Up to 80 PSI
- Warranty period: 2 years

FLEX^{SG} TUBING

Features

- Engineered to resist kinking
- Textured for easy grip
- Linear low-density polyethylene material
- Meets ASTM D2104, D2239, D2737

Models

- FLEX^{SG}: 100' roll
- FLEX^{SG}-18: 18" pre-cut lengths

Operating Specifications

- Operating pressure: up to 80 PSI
- Warranty period: 2 years

PRO-SPRAY SHUTOFF CAP

Features

- Caps off the Pro-Spray for maintenance or drip conversions
- Maintains a clean look to the landscape

Models

- 213600SP

SHUTOFF NOZZLE

Features

- Easy shutoff for spray systems
- Allows heads to pop-up for easy visibility
- Use with Pro-Spray and PS Ultra models

Models

- 916400SP



SJ Swing Joint

6" and 12" links



Spiral Barb Elbows

P/N HSBE-050, P/N HSBE-075



FLEX^{SG} Tubing

100' and 18" pre-cut lengths
Inside diameter: 0.49"



Pro-Spray Shutoff Cap

213600SP



Shutoff Nozzle

916400SP