



**LEGEND:**

- ① ECO-WRAP PER PLAN
- ② ROCK PAVERS
- ③ FLUSH POINT (PLD-BV) IN SUBTERRANEAN BOX PER PLAN
- ④ AIR RELIEF VALVE IN VALVE BOX
- ⑤ ECO-INDICATOR ON SWING ARM
- ⑥ PLD OR PLD-LOC FITTINGS TYP.
- ⑦ DRIP CONTROL ZONE KIT PER PLAN

**NOTES**

AIR RELIEF VALVE (PLD-AVR) INSTALLED IN VALVE BOX AT OPTIMAL HIGHEST POINT FROM CONTROL ZONE KIT. MULTIPLE AIR RELIEF VALVES MAY BE NEEDED TO ACCOMMODATE DIFFERENCES IN GRADE.

ECO-INDICATOR TO BE INSTALLED AT OPTIMAL FURTHEST POINT FROM CONTROL ZONE KIT IN CLEAR VIEW WHEN POPPED UP.

FLUSH POINT TO BE INSTALLED AT OPTIMAL FURTHEST POINT FROM CONTROL ZONE KIT TO ALLOW FOR MAXIMUM DEBRIS FLUSH IN SYSTEM.



**ECO-WRAP - BETWEEN ROCK PAVERS**

**Hydrex** HM.EM.19

NOT TO SCALE