
TECHNICAL ASSISTANCE 1-800-319-4796 WWW.HUNTERINDUSTRIES.COM

VALVE IDENTIFICATION GUIDE

SYMBOL	MANUFACTURER/MODEL/DESCRIPTION	QTY
•	Hunter ICV-G 50mm 25 mm, 40 mm, 50 mm, and 80 mm Plastic Electric Remote Control Valves, Globe Configuration, with NPT Threaded Inlet/Outlet, for Commercial/Municipal Use.	10
BF	Watts 919QT 50mm Backflow reduced pressure zone	1
М	Water Meter 50mm	1
-	Irrigation Lateral Line: PVC Class 200 SDR 21	233.3 r
	Irrigation Lateral Line: PVC Class 200 SDR 21 40	247.0 r
	Irrigation Lateral Line: PVC Class 200 SDR 21 50	138.8 r
	Irrigation Lateral Line: PVC Class 200 SDR 21 80	83.3 m
	Irrigation Mainline: PVC Schedule 40 80	49.1 m
	Irrigation Mainline: PVC Schedule 40 100	68.7 m



IRIRGATION LEGEND

A9 210

Scale: 1:400

A2 210

A3 234

SYMBOL	MANUFACTURER/MODEL/DESCRIPTION	QTY	kPa	l/min
25)	Hunter I-50-06-SS Turf Rotor, 15 cm Pop-Up. Adjustable to Full Circle. Drain Check Valve, Stainless Steel Riser, 25 mm Female NPT Inlet Threads, Standard Nozzle.	16	551.6	104.9
(28)	Hunter I-50-06-SS-ON Turf Rotor, 15 cm Pop-Up. Adjustable to Full Circle. Drain Check Valve, Stainless Steel Riser, 25 mm Female NPT Inlet Threads, Dual Opposing Nozzle.	8	551.6	117.0

A6 \419

A4 419

Hunter Industries offers this plan as a general guide for estimating purposes and offers no indemnity, expressed or implied, for projects installed from this plan. Consult a qualified irrigation designer to account for system and site variables.